

NEEDLE PUNCHED YARNS

5

FIELD OF INVENTION

The present invention generally relates to the processing of yarns, in particular, the present invention relates to spun filament or fiber yarns processed through a needling process to interlock or link the yarn filaments or fibers together.

10

BACKGROUND OF INVENTION

15

20

25

In yarn manufacturing, yarns generally are spun from one or more fibers, including natural and/or synthetic fibers, using conventional ring, open-end, air-jet, worsted, woolen, or Dref spinning processes. The yarns then are used in a single form or ply or are plied together with other yarns or filaments to produce a single but bigger yarn. One of the principal problems with spun formed yarns generally is the tendency of such yarns to unravel or fray when cut, and, depending upon the method of spinning, such yarns generally will have inherently low abrasion qualities. To try to solve this problem it has generally been known to add a low-melt fiber or filament, as a percentage, into the mass yarn bundle. Thereafter, following completion of the spinning and/or twisting process, when the yarns are processed through a heat-set range, they are generally exposed to temperatures and dwell times that melt the low-melt fibers into an adhesive that bonds the fibers and/or plies of the yarn(s) together. Other methods of solving the unraveling or fraying problem typically consist of adding adhesives to the finished yarn in a costly after-process that also tends to deter their natural surface characteristics.

One example of yarn products where the problem of unraveling and/or diminishment of surface characteristics are especially problematic is mops. Mops usually consist of one or more spun yarns containing cotton and/or other fibers of good absorption and abrasion properties, twisted as a single yarn in a Z rotation. These yarns are then grouped or plied with 2 to 32 ends of the same type yarn or other yarns of different structures or compositions and are twisted in an opposite rotation until the yarn is balanced. Such yarns generally have good absorption properties and are preferred in the janitorial field. However, by their inherent structure, these mops typically tend to unravel or lint as they are used. This shortens the usable life for the mop and tends to cause lint to be distributed on and thus diminish the finish of cleansed surfaces.

To combat this, mops made of non-woven strips have been introduced into the market. These strips are manufactured by carding and forming a fiber mass and adhering it together by adhesives or by thermal bonding. This process, however, tends to diminish or lessen the absorption properties of the mop. Further, while the use of many synthetic fibers has yielded products, such as mops, that have good abrasion properties, such products often do not have good absorption or wicking properties, particularly where the fibers are pressed or tightly linked together.

It is therefore seen that a need exists for an economical means of interlocking fibers and plies of spun yarns or filaments together to form yarns that exhibit better abrasion resistance and wicking, do not unravel as quickly, and have a longer usable life.

SUMMARY OF THE INVENTION

The present invention is directed to the formation of yarns, cordage and/or fibrous mats or bundles having enhanced strength and resistance to unraveling, and which link the properties of both spun yarns or fibers having, for example, good absorption, to other materials such as nonwoven strips having, for example, good abrasion properties, but low absorption. The resultant spun yarns, therefore, will be provided with the enhanced absorption properties of a natural or woven fiber yarn and the durable and less-linting properties of a non-woven material yarn.

Typically, the yarns are spun from a series of natural and/or synthetic fibers to form a yarn bundle or fibrous mass, and generally include core fibers wrapped or covered with sheath fibers. The yarns are fed from creels or beams along a feed path into a loom or needling apparatus or system, being pulled through the loom under tension. The yarns are each fed along a milled groove of a needle plate of the loom. Each groove has sloped sides defining a guide channel that is aligned with the feed path and a centerline of each of the yarns, and which direct the yarns downwardly and toward the center of the guide channels, so that their centerlines are aligned along the feed path as the yarns are moved through the loom.

The loom generally includes a drive plate or carrier that is reciprocally driven toward and away from the yarns passing through the grooves of the needle plate. A series of needles are arranged in spaced, parallel rows or lines of needles on the drive plate, with each of the needles typically having one or more barbs adapted to catch or pull portions of the core and sheath fibers of the yarns through the yarns as the needles are reciprocated into and out of the yarns. Each row of needles is aligned substantially

directly perpendicular to the centerline of one of the yarns in the grooves so as to penetrate the yarns substantially along their centerlines and pull fibers through the yarns to substantially intermix and interlock the core and sheath fibers of the yarns. The grooves of the needle plate typically are formed with sufficient depth and slope to enable additional yarns to be stacked therein with the yarns maintained substantially parallel with their centerlines in alignment with a row of needles. The guide channels further can be arranged in substantially flat, straight configurations, or curved or arcuate configurations or construction with the needles likewise being carried by a drive plate having a similar shape or configuration so that rows of needles substantially matches that of the guide channels.

In a further embodiment, a fibrous mat can be fed along or over the yarn guides, being run parallel to the yarns for needling and attaching the yarns to a fibrous mat. Strips of material also can be attached to the yarns by positioning the strips over the yarns in the guide channels of the needle plate so that as the needles pierce the fibrous strips or webs and the yarns, fibers from the yarns, and the strips or webs are intermixed and become substantially interlocked so as to form a composite yarn/strip. As a result, composite material strips, and/or mats can be formed which incorporate different properties of one or more different types of yarns, such as, for example, combining the absorbency of a cotton or similar natural fiber yarn with the abrasive properties of a synthetic or man-made fiber, so as to create a yarn that has high absorbency and good abrasive capabilities but which does not have a tendency to lint or unravel easily, especially after repeated exposure to water and other liquids.

Various objects, features and advantages of the present invention will become apparent to those skilled in the art, upon a review of the following detailed description, when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a yarn, illustrating the core and sheath fibers.

Fig. 2 is a schematic view illustrating the feeding of yarns from yarn creels through a loom.

Fig. 3 is a side elevational view, schematically illustrating the passage of a yarn through one of the yarn guides for engagement by the needles of the present invention.

Fig. 4 is an end view illustrating the movement of yarns through the yarn guides, with the needles being substantially aligned along the centerlines of the yarns.

Fig. 5A is a side elevational view with parts broken away, illustrating the engagement of the needles with a yarn passing through an arcuate yarn guide.

Fig. 5B is an end view illustrating the penetration of a needle into two parallel yarns.

Fig. 5C is a side elevational view of a pair of welded, interlocked yarns according to the present invention.

Fig. 6 is a perspective view illustrating an additional embodiment of the present invention in which fibrous mat or web is attached to yarns being passed through the yarn guides.

DETAILED DESCRIPTION

The present invention relates to needle-punched yarns 10 (Fig. 1), cordage and fiber mats or bundles having improved or enhanced natural properties relating to strength, absorption, resistance to unraveling, and linting, and for desired aesthetic patterned appearances or features. The yarn typically is a spun yarn in a multi-ply or single-ply form, and generally includes one or more core fibers or filaments, or a series or mass of fibers 11 not necessarily having or requiring a core fiber. A covering or wrapping of cover or sheath fiber(s) 12 are wrapped or spun around and substantially cover the core fiber(s) to form the fibrous mass or yarn bundle. The yarns generally can be spun by means of ring, open-end, worsted, woolen, air-jet, or any other type spinning process, can include carded webs or fibers such as a worsted carded web or can be spun or carded in a synthetic filament form, however, it has been found that the more disoriented the fibers are in the yarn, the more effective the present invention. Dref or friction spun yarns further generally display a greater degree of improvement than open-end, ring spun, or vortex spun yarns, although such other types of yarns also can be used in the present invention. The core and sheath fibers of the yarns can be composed of natural fibers, such as cotton, wool, and the like; manmade or synthetic fibers, such as nylon, aramids, polypropylenes, polyesters, rayon, acrylics, polyethelenes, para-aramids, plastics and the like; or combinations thereof, and typically consist of micro-denier fibers up to coarse fibers of approximately 15 – 20 denier.

As shown in Fig. 2, the yarns generally are fed from creels 13 along a feed path 14 into a needle loom 16, either as single ends off of creel cones 13 or incorporated together as on a beam. The loom 16 typically is a needling loom such as a Fehrer H-1

needle loom or similar needling apparatus or system. As shown in Figs 3 and 4, the loom 16 generally includes a reciprocably moving needle carrier or drive plate 17 that carries a series of needles 18, and a needle bed plate 19 positioned directly below the carrier or drive plate 17. The needles generally are polished needles having one or more barbs 21 and a polished surface, and are arranged in defined, spaced rows or lines of needles along the length of the carrier 17. The spacing of the needles generally ranges from about 5mm to about 10mm, typically approximately 7 mm, although spacings of less than 5mm and greater than 10mm also can be used, with the rate of advance of the yarns generally determined by the spacing such that the yarns are typically advanced a distance per each needle stroke approximately equal to the needle spacing. The spacing of the needles and the feed rates of the yarns passing along the needle plates can be varied, as can the size and number of barbs of each needle, to vary the engagement of the fibers of the yarns by the needles.

As the yarns enter the loom, each yarn end is fed along its feed path 14 into and along a ceramic or plastic yarn guide 22 (Fig. 3), such as an eyelet or other, similar type of guide, with the yarns fed under tension so as not to get tangled up with neighboring yarns. As the yarns enter the yarn guide 22 (Figs. 3 – 4) the yarns are each directed into milled grooves 23 that have been milled or formed in the needle bed plate 19 (Fig. 3) of the loom. The grooves are formed with sloping sides 24 that define guide channels 26 along which the yarns are moved with the centerlines 27 of each of the yarns being aligned parallel to each other and the feed path 14. The yarns generally are kept taut or under tension in the grooves with a changeable/variable positive draft as they are drawn through a needling zone 28, such as by using tension rolls 29 to pull the yarns through the

loom. The yarn guides further generally are positioned lower than the milled grooves 23 so the tension applied to the yarns keeps each yarn within its respective groove.

As indicated in Fig. 4, the needles 18 of each line of needles on the carrier or drive plate are positioned so that they are directly perpendicular with an axis or centerline 27 of one of the yarns traveling through one of the grooves of the needle bed. This ensures that the barbs of the needles will penetrate substantially through the cores 11 and sheath fibers 12 of the yarns and not through the edges of the yarns where the needles could miss the cores and thus the needling would be less effective and would also tend to cause fuzzing or distortion of the yarn. As the needles penetrate the centerlines of the yarns, the barbs of the needles tend to urge and engage and pull fibers from the core and sheath fibers through the body of the yarn, i.e., through the core and sheath fibers, so as to cause an intermixing of these fibers. Thus, portions of the core and sheath fibers become intertwined and thus interlocked to create a yarn that is generally more resistant to unraveling and linting, even when cut and/or exposed to liquids, since the fibers are locked together, without requiring application of adhesives or expensive after processing to set the yarns, which later processes and additives can also affect the material properties of the yarns. It has also been found that if the yarn is pulled from individual packages, and unwound from the top of the cone or tube, the natural tendency of the yarn to twist as it proceeds through the needle loom amplifies the effectiveness of the needle penetration therethrough.

The present invention can use a straight, substantially horizontal, flat needle bed 19 (Fig. 4) or a curved needle bed (Fig. 3), such as used in a Fehrer H-1 needle loom. In the use of a curved needle bed, the yarns generally are subjected to about a 0° to 20° angle

arc with respect to the needles (Fig. 4), although greater or lesser arcs also can be used as desired. The use of an arcuate bed tends to give a longer stroke of the needles through the yarns and thus typically increases the effectiveness of the needles capturing and pulling fibers through the yarns for interlocking the core and sheath fibers. The needles, because of the curvature of the needle bed, penetrate the yarn at multiple angles within the arc, which increases the fiber interlocking within the fibrous body of the yarns 10 as shown in Figs. 1 and 5A. This not only increases the effectiveness of the needle penetration and pulling of the fibers, but also accomplishes higher output speeds for yarns processed according to the present invention. Thereafter, upon exiting the needle bed, the yarns proceed through the tensioning rollers 29 (Fig. 2 and 3) and then are either taken up on individual tubes or cones 31 (Fig. 1) or are grouped together on a warper or beam for further processing.

The dwell time of the needles within the yarn or fiber mass, the speed at which the yarns are advanced through the needle bed and the rate or aggressiveness of the penetrations of the yarn by the needles further can be controlled as needed or desired to provide the finished yarns with certain design properties. For example, the dwell time of the yarn within the needling zone of the yarn and/or the penetration rate of the needles through the yarns can be increased, such as by slowing the advance rate of the yarns per stroke of the needles to less than the spacing of the needles and increasing the rate at which the needles are reciprocated, so that the fibers or filaments thereof are pulled and mixed to a greater extent such that the overall diameter of the finished yarn is significantly increased. Such enhanced bulk is particularly useful for forming lighter weight yarns for use in applications such as blankets or filtration systems where greater

bulk or surface area is desirable, or for use in forming fire block barriers using aramid, para-aramids or melamine fibers yarns, such as Basofil®.

Alternatively, various patterns or aesthetic features or effects can be formed in the yarns by varying the feed rate or amount by which the yarns are advanced through the needling zone. For example, the yarns can be formed with a spiral or corkscrew effect by advancing the yarns a distance approximately equivalent to the horizontal spacing between the needles following each stroke of the needle. This effect can be further enhanced or varied by advancing the yarns by some multiple of the needle spacing, i.e., twice the spacing or greater, and by increasing the twist of the yarn being fed from their creels.

Additionally, the milled grooves 23 of the needle plate further typically are milled to a depth sufficient, and have side walls 24 of a sufficient spacing, such that two or more yarns 10, 10' (Fig. 4) can be fed on top of one another with their centerlines 27 aligned with each other and with a line of needles as indicated in Fig. 4. The penetration of the needles through both of the aligned or parallel stacked yarns causes an intermixing of the fibers of the two yarns 10 and 10' so as to produce a composite yarn that has two yarns welded or joined together along their central axis or center line. The resultant composite yarn has a greater surface area than if the two yarns simply had been plied or spun together (Figs. 5B – 5C). The present invention thus can be used to form welded yarns wherein yarns of different material types are attached or welded together, as opposed to being twisted together to form a multi-ply yarn, as shown in Fig. 5C. For example, to combine a polypropylene yarn having good wicking properties and a cotton yarn with good absorption the yarns are received within their yarn guides with one yarn laid one on

top of the other in the yarn guide. As the needles punch through the yarns, they intermix and interlock the fibers to form a side-by-side double strand yarn with each of the yarn components 10 and 10' (Fig. 5C) having more exposed surface area over a conventional twisted multi-ply yarn.

5 A further embodiment of the present invention is shown in Fig. 6. In this embodiment, as the yarns are moved through the needle loom, a fiber mass or fabric 40 can be incorporated with the yarns. The fiber mass generally will be formed from natural or synthetic fibers, or a combination thereof, and is fed in a blanket or sheet from a feed roll 41 along the feed path 14 of the looms, the fiber mass 40 will be fed between the
10 needles and the yarns, with the yarns passing along the milled grooves of the needle plate bed on which the fiber mass is moved. The yarns are guided into and along the grooved slots in the needle bed and controlled by the positive tension draft placed on each yarn so as to maintain their alignment with the needles. As the needles penetrate through and are drawn out of the fiber mass and yarns, the barbs of the needles engage and pull fibers of
15 the mass 40 and the yarns 10 so that these fibers become intermixed and interlocked to produce a fabric or composite material with increased dimensional stability and desired properties. Additionally, the fabric mass 40 could be split, such as along dashed lines 42, to form separate fibrous strips 43. Each strip can then be incorporated with or become an integral part of the yarns, bringing different desirable properties and characteristics to the
20 yarns.

Yet another example of the present invention is the advancement and perfection of engineered yarns having various specifically designed properties. These yarns incorporate a core of slit film, multi-denier filaments or a textured filament made of

polypropylene, nylon, polyester, aramid, rayon, acrylic, or polyethene wrapped or sheathed with fibers of cotton, synthetics, or combinations thereof. These yarns will be processed through the needle loom, wherein the needles of which will penetrate the filament and entangle the wrapper fibers, so that they become a single entity and to
5 substantially ensure that that the sheath fibers will not slide along the axis of the yarn.

The resultant yarns can be used for a variety of uses, such as for mops or making into mats for abrasive pads or other uses, and have increased strength and absorbency, while also exhibiting better abrasiveness and resistance to unraveling and releasing lint. Yarns having high absorption properties, such as cotton yarns, can be combined with
10 yarns having enhanced abrasive properties to provide mop yarns with enhanced liquid absorption and scrubbing properties. The present yarns accordingly are provided with the finished appearance and properties of high end yarns while being capable of being formed by less expensive spinning processes.

Example 1

15 Two yarns were manufactured for Example 1. In the first sample (No. 1), .60 cotton count open-end spun (OE) and Dref spun yarns consisting of 34% rayon, 33% polyester, and 33% cotton were formed. The rayon was a 3 denier x 2 inch fiber manufactured by Lenzing Corporation. The polyester was a 1.5 denier x 1.5 inch length manufactured by KOSA. The cotton was of a mill waste blend with fibers ranging in
20 length from 1 inch to 1/8 inch. These fibers were blended, carded, and open-end spun on a 130 mm rotor, Reiter spinning machine with a 4.0 twist multiple. Four ends were then parallel wound on a tube and twisted on an ICBT two for one twister with an S twist.

The second sample (No. 2) consisted of .60 cotton count Dref spun and open end spun yarns composed of mill waste cotton, with fiber lengths of 1 inch to 1/8 inch and being of a cotton polyester blend. The fibers were prepared as in the previous sample through blending and carding. The fibers were then fed into a Dref II spinning frame and spun with a Z twist comparable to the open-end spun yarn. The yarns were then plied as before with an S twist.

Each type of yarn of each sample was then processed through a Fehrer H-1 needle loom. The yarns of Sample No. 1 were processed at a speed of approximately 40 meters/min with the needles being reciprocated at about 1300 revolutions/min to give a puncture rate of about 1365 needle punctures/meter. The needle bed was formed in an arch design, with the needles generally having a penetration depth of 10mm and being positioned at varying degrees of penetration about an arc of about +20 to 0 to -20. The preferred needle used was a Foster 15 x 18 x 36 x 3RBAF .20 6-4B polished. The needles were arranged in the bed in a straight line and the yarn was guided into the H-1 needle loom by ceramic eyelets that directed the yarn into the milled grooves of the needle plate, which grooves kept the yarns positioned directly under the needles. The yarn was then rewound onto tubes.

The yarns of Sample No. 2 also were processed through a Fehrer H-1 needle loom at 60 meters/min. The needle bed revolutions were 1300/min. totaling 900 needle punches/ meter. The same Foster needle was used, however the penetration depth was increased to 14mm.

A small reeling of each yarn was tied into a bundle having a total length of approximately five inches. One control yarn reeling of a conventional with no needling,

one of each of the Sample No. 1 OE and Dref yarns, and one each of the Sample No. 2 OE and Dref yarns were prepared. The sample yarns and control yarns were then placed into the AATCC standard Kenmore washing machine with varying amounts of warm water and ½ cup of Tide household detergent. A different sampling was used for each test.

Wash test of control and Sample Nos. 1 and 2 needle punched OE and Dref spun mop yarns - July 6, 2000

7 minute agitation in washing machine, medium water level

Sample	No.	color	results
1. .60/4 OE spun	Control	yellow	complete unraveled/partial degradation
2. .60/4 OE spun	No. 1	orange	unravel .25 to .75 inch
3. .60/4 OE spun	No. 2	teal	unravel 1 to 1.5 in
A. .60/4 Dref spun	Control	none	unraveled and complete degradation
B. .60/4 Dref spun	No. 1	black	0 to .25 inch unraveled
C. .60/4 Dref spun	No. 2	Lt. green	.25 to .5 inch unraveled

12-15 minute agitation in washing machine, medium water level

Sample	No.	color	results
1. .60/4 OE spun	Control	yellow	complete degradation
2. .60/4 OE spun	No. 1	orange	1 to 1.5 inch unraveled approx. ½ inch loss length
3. .60/4 OE spun	No. 2	teal	unravel 1 to 1.5 inch
A. .60/4 Dref spun	Control	none	complete unravel 2/3 loss of fiber
B. .60/4 Dref spun	No. 1	black	unravel .25 to .5 inch loss ½ to 1 inch in length
C. .60/4 Dref spun	No. 2	Lt. green	unravel .25 to 1 inch no loss of length

15-20 minute HIGH agitation in washing machine, Low water level

Sample	No.	color	results
1. .60/4 OE spun	Control	yellow	complete degradation, loss of ½ of fiber mass
2. .60/4 OE spun	No. 1	orange	unravel .25 to 2 inch approx. ½ inch loss in length

3.	.60/4 OE spun	No. 2	teal	unravel 1 to 2.5 inch , approx. ½ to 1 inch loss in length
5	A. .60/4 Dref spun	Control	none	complete degradation, massive fiber loss
	B. .60/4 Dref spun	No. 1	black	unravel .25 to 1 inch, approx. ½ to 1 inch in length
	C. .60/4 Dref spun	No. 2	Lt. green	unravel 1 to 2.5 inch, approx. ½ to ¾ inch loss in length

CONCLUSION:

The open-end spun yarns and Dref spun yarns processed by the present invention out-performed the unprocessed, unneeded control yarns with the open-end spun yarn samples exhibiting better resistance to unraveling than the Dref spun yarns. The Dref spun yarns processed with the present invention did, however, still exhibit significantly greater performance and resistance to unraveling and loss of fiber than the open-end yarns of the control sample.

EXAMPLE 2

A yarn of an open-end design was used, composed of 60% Lenzing 3 denier x 2 inch rayon fiber blended with 20% Kosa 2 denier x 2 inch polyester fiber and 20% Sterling 3 denier x 2 inch natural acrylic fiber. The yarns were processed through a fiber control opening line, Crosrol Mark 5 carding machine and spun on a 100mm rotor to a 1/1 cotton count yarn with a 4.0 twist multiple. Four identical ends were then parallel wound onto a tube and twisted on a Volkman 05 two for one twister.

A portion of this yarn was then processed through a Fehrer H-1 needle loom. The yarn was processed through the loom as before, and was contained within the grooves of the needle bed. The preferred needle was a Groz-Beckard 15 x 18 x 38 x 3 222G.

Because of the open-end yarn construction and the smaller size and total yarn mass as compared with Example One, a smaller gauge needle with a more aggressive barb structure was preferred. The yarn traveled through the needling zone at about 10 meters per minute. This yielded an estimated approximately 5410 needle penetrations per meter of yarn with the needles being reciprocated at about 1300 revolutions per minute at about a 13mm penetration depth.

Three reelings of before needling and after needling yarn samples were prepared. These reelings measured approximately five inches in length and the yarns of each sample were cut at one end to resemble a cut-end mop. The sample reelings were then placed into a standard AATC Kenmore washing machine filled ½ full of warm water and one cup of Tide household detergent. The normal heavy washing agitator cycle was used.

minute agitation in washing machine, medium water level

Sample	Results
15 ¼ rayon blend without needling	yarn completely untwisted
¼ rayon blend with needling	no change in appearance

10 minute agitation in washing machine, medium water level

Sample	Results
20 ¼ rayon blend without needling	yarn untwisted, some fiber loss
¼ rayon blend with needling	no change in appearance

30 minute agitation in washing machine, medium water level

Sample	Results
25 ¼ rayon blend without needling	yarn untwisted, increasing fiber loss
¼ rayon blend with needling	no change in appearance

CONCLUSION:

The ¼ rayon blend yarn is a generally preferred yarn in the janitorial field for the application of floor finishes. This application, however, requires the mop to release little,

if any lint. This test thus shows how the needling process of the present invention greatly improved the performance of this yarn in not only in the degree of linting but also increasing the life of the mop.

It will be understood by those skilled in the art that while the invention has been
5 described above with reference to certain embodiments and examples, numerous changes, additions and modifications can be made and various equivalents substituted without departing from the spirit and scope of the invention as set forth in the following claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222